



PS900



S900 STD



S901 SS



S903 SS

saladettes

Functional and durable saladette
counters in two and three door versions
offering four top options.



S903 STD



saladettes

- > Complete structure in stainless steel AISI 304.
- > Foamed on the back and two sides to 50mm insulation thickness.
- > Recessed door handles with rounded and smooth edges for safety and ease of cleaning (A).
- > Easily replaceable magnetic door gaskets (B).
- > Bottom mounted condensing unit, easy to service.
- > Easily accessible condenser filter for easier cleaning (C).
- > Automatic defrost and evaporation of condensate water.
- > Internal ventilation ensures even temperature distribution.
- > Internal coved corners for increased hygiene (D).
- > Adjustable feet.
- > Spare space for shelves and pans GN1/1.
- > Two drawer option available (E).
- > Advanced electronic control from brand leader Carel.

NB gastronorm pans do not come with the unit.



(A)



(B)



(C)



(D)



(E)

	S900 STD	S903 STD	S901 SS	S903 SS	PS900
External Dimensions W x D x Hmm	900 x 700 x 850	1365 x 700 x 850	900 x 700 x 850	1365 x 700 x 850	900 x 700x 1075
Internal Dimensions W x D x Hmm	830 x 515 x 500	1295 x 515 x 500	830 x 515 x 500	1295 x 515 x 500	830 x 515 x 500
Nett Capacity - Litre	240	368	240	368	288
Shelves	2	3	2	3	2
Voltage Hertz	230/50	230/50	230/50	230/50	230/50
Compressor Size	7.5cc	8.85cc	7.5cc	8.85cc	7.5cc
Weight Empty	70kg	107kg	72kg	107kg	70kg
Max. Power Consumption Watt per 24Kwh/24h	3	3.8	2.8	3	3
Temperature Range	+2/+8°C	+2/+8°C	+2/+8°C	+2/+8°C	+2/+8°C
Refrigerant Gas	R134a	R134a	R134a	R134a	R134a
Insulation Gas	CFC free	CFC free	CFC free	CFC free	CFC free
Insulation Thickness	35mm	35mm	35mm	35mm	35mm
Maximum Ambient Temperature	38°C	38°C	38°C	38°C	38°C
Exterior Material	S/S AISI304	S/S AISI304	S/S AISI304	S/S AISI304	S/S AISI304
Interior Material	S/S AISI304	S/S AISI304	S/S AISI304	S/S AISI304	S/S AISI304

Rhino produces commercial refrigeration products for the professional caterer, combining the highest standards of hygiene with the latest construction and control technology.

Staycold Export Ltd.
 9 Hunters Walk, Canal Street, Chester CH1 4EB. United Kingdom
 Telephone: +44 (0)1244 321320
 Fax: +44 (0)1244 322345.
 e-mail: info@rhinoequipment.eu



www.rhinoequipment.eu